



Food contact compliance statement

We, Meda-Pak, hereby declare that the product we deliver to your company, referenced POLY, belonging to the pe film range, is produced under Quality and Hygiene certified Management System:

- Quality: ISO 9001 :2000 by AFAQ (Association Française pour le management et l' Amelioration de la Qualite)
- Hygiene: BRC/IoP Hygiene Standards including HACCP by LNE (French National Laboratory for Tests)

We declare that this plastic film fully complies with the E.U. legislation in force (regulation (EC) No.1935/2004, 2023/2006) concerning materials and articles intended to come into contact with food and in particular with the regulation (EU) no. 10/2011/EC (and its amendments) relating to plastic materials and articles.

The above mentioned product contains substances restricted by a specific migration limit (SML). The content of these substances does not exceed the SML by a maximum thickness of 180 microns of the packaging (theoretical worst case scenario). Substances also authorized as a direct food additives (Dual use additives) are either not used for the manufacturing of this product, kind of not migrating, or only present in quantities that in case of their migration don't allow relevant contribution to exceed of the limit as set in the applicable food legislation. EU regulation 10/2011/EC limits the permissible overall migration limit 10 10 mg/dm². Several formulations of food packaging film (colored and/or printed) are tested on the contact side / non printed side and meet the overall migration limit under the following test conditions for long term food contact storage at room temperature:

Simulant	Test Conditions	Global migration	Food Type
10% Ethanol	10 days at 40 ° C	< 2,5 mg/dm ²	Aqueous
50 % Ethanol	10 days at 40 ° C	< 2,5 mg/dm ²	Alcoholic
3% Acetic acid	10 days at 40 ° C	< 2,5 mg/dm ²	Acidic
Olive oil	10 days at 40 ° C	< 2,5 mg/dm ²	Fatty


It should be noted that the product has been tested for the above mentioned forms of usage and conditions. Therefore, it will be the sole responsibility of the downstream users to determine that the usage of the product complies with the information given in this document and is safe, lawful and technically suitable so that no change in flavor, taste or organoleptic properties occurs. In case the product will be used in a different manner than tested, the information in this declaration of compliance will not apply and the downstream users shall be responsible for the compliance with the specific legislation and regulations.

Food packaging film should be stored dry at ambient temperature in a warehouse, not exceeding 40 ° C. Packaging should be kept intact during storage. Do not expose to direct sunlight. Under these conditions shelf life is 6 months.



Meda-Pak BV C.Verolmelaan 95 1422 ZB Uithoorn-NL T +31(0)297-582 757 F +31(0)297-582 758 M info@medapak.nl I www.medapak.nl

This film is suitable for:



Cheese




Meat




Fish



Fruit, vegetable
And frozen product




Sandwich



Freezer (-30°C mini)


This film is NOT suitable for:




Pure fat and oil



Margarine and butter



Micro-wave oven



Traditional oven, infrared oven
and multi purpose oven

The recipient should pay particular attention to any change in the packaged product, its intended use and also to any modification in the material's processing conditions and make sure that the contents and packaging are compatible, as directed in this declaration.

This certificate is only valid when the film is used in normal and foreseeable conditions, provided that the handling and storage conditions are also appropriate for preservation of the material's specific characteristics.

Date:
4-1-2022

Quality
Manager

Issued by an electronic system



Compliance statement with European Directive 94/62/EC

Product's identification concerned by this attestation: POLY

Supplier's assessment reference: ELWW040

Part 1: Summary of assessment

Standard / Report	Assessment requirement	Claim	Note
1.1 Prevention by source reduction	ensure only minimum adequate amount of material in the packaging system (EN13428)	yes	<i>This product is manufactured according to customer specifications: thickness and width are minimized to suit the use, length cut will depend on the application.</i>
1.2 Heavy metals and	a. ensure below maximum permitted levels for components (CR 13695-1)	yes	<i>The sum of concentrations of lead, cadmium, mercury, hexavalent chromium does not exceed 100 ppm</i>
1.3 other noxious/ hazardous elements	b. ensure in compliance with Annex 1 of Directive 67/548/CEE (EN13428)	yes	<i>None hazardous element is introduced or included over the level of impurity</i>
2 Reuse	ensure re-usability in all terms of the standard for the packaging (EN 13429)	no	<i>The use of our products forces their modification (by cutting, welding ...) ; no re-use is conceivable</i>
3.1 Recovery by material recycling	ensure recyclability in all terms of the standard for the packaging (EN13430)	not applicable	<i>Cleaning of our products after food contact would be too expensive and non-ecological.</i>
3.2 Recovery in the form of energy	ensure that calorific gain is achievable for the packaging (EN13431)	yes	<i>"Packaging made of over 50% of organic material ... must be considered as energetically recyclable" (EN 13431:2000). This is particularly true for light plastic packagings.</i>
3.3 Organic recovery	ensure compostability in all terms of the standard ~or the packaging (EN13432)	not applicable	<i>Conventional plastic materials are not suited to compost.</i>

Note: Conformity with EN 13427 requires affirmative responses to §1.1, 1.2 & 1.3 and to at least one of §3.1, 3.2, 3.3. In addition, where a claim of reuse is made, section 3 should also record affirmative responses.

Data to justify this evaluation will not be transmitted by Meda-Pak but kept at the government agent's disposal

Part 2: Statement of conformity:

In the light of the assessment results recorded in part 1 above, the referenced product is claimed to comply with the requirements of EN 13427. This means it is presumed in conformity with the essentials requirements of packaging regulations 94/62/CE.

Quality manager

* Supplier as defined in EN 13427

Document established under the recommendations of the norm EN 13427
Issued by an electronic system



Meda-Pak BV C. Verolmelaan 95 1422 ZB Uithoorn-NL T +31(0)297-582 757 F +31(0)297-582 758 M info@medapak.nl I www.medapak.nl

POLY

PE FILM FOR FOOD PACKAGING

		Unit	Method	Value	
		<i>Unite / Unidad / Unità / Masseinheit</i>	<i>Methoda / Methoda / Metoda / Verfahren</i>	<i>Valueur / Va/or / Valore / Wert</i>	
General characteristics					
Colour <i>Couleur / Color / Colore / Farbe</i>		/		neutral / white	
Thickness <i>Epaisseur / Espesor / Spessore / Dicke</i>		my		20,0	+/- 10%
Range of length <i>Longueur / Largo / Lunghezza / Lange</i>		m		50-300	-0 / +1,5%
Range of width <i>Large / Ancho / Fascia / Breite</i>		mm	Meda-Pak	300	+/- 5mm
Standard core <i>Mandrin / Mandri / Mandrino / Kern</i>		mm		38/48-335	mm
Tensile characteristics					
Machine Direction (MD)	Strength	N/mm ²	ASTM D882	23	mini
	Elongation	%		228	mini
Cross Direction (CD)	Strength	N/mm ²		21	mini
	Elongation	%		562	mini
Permeability properties					
Oxygen transmission (O ₂)		cm ³ /m ² .24h.bar		180 15105-2 (23°C;0%RH)	31000 +/- 20%
Carbon dioxide transmission (CO ₂)		cm ³ /m ² .24h.bar		180 15105-2 (23°C;0%RH)	111000 +/- 20%
Water vapour transmission (H ₂ O)		g/m ² .24h.bar		180 2528 (23°C;75%RH)	13 +/- 20%

Automatic : no

automatique / automatico / automatico / automatisch

Manual : yes

manuelle / manual / manuale / Manuell

Remarks

- Optimal storage conditions: 15/20°C away from humidity. Film properties may be altered in extreme storage conditions.
-We recommend use of our films within a delay of 6 months after delivery for the Polyolefin range and 12 months for PVC range.
-The figures in this document are given for information only.

- Condizioni ideali di stoccaggio : 15/20°C a (l)bi de l'umidità. Le proprietà del film possono essere modificate in condizioni di stoccaggio estreme.
-Nous recommandons une utilisation de nos films dans un délai maximum après livraison de 6 mois pour la gamme Polyolefin et de 12 mois pour la gamme PVC.
-Les informations contenues dans ce document sont données à titre indicatif.

- Condiciones de almacenamiento óptimas : entre 15 y 20 °C protegiendo de la humedad. Las propiedades de la película pueden sufrir alteraciones en condiciones de almacenamiento extremas.
-Recomendamos una utilización de nuestros films en un plazo máximo después de la entrega de 6 meses para la gama Polyolefin y 12 meses para la gama PVC.
- La información técnica en este documento se ofrece a título indicativo.

- **Nota di stoccaggio:** 15/20°C in ambiente non umido. Le proprietà del film possono essere modificate in condizioni di stoccaggio estreme.
- **Raccomandiamo l'uso del** film in un **tempo massimo** di sei (6) mesi dopo la consegna per la gamma Polyolefin e di dodici (12) mesi per la gamma PVC.
- Le informazioni di questo documento sono indicative.

- Optimale Lagerbedingungen : 15/20°C, trocken (ggf) von Feuchtigkeit fernhalten. Die Kondition der Frischhaltefolie kann sich bei extremen Lagerbedingungen ändern.
-Wir empfehlen unsere BRC-Folien innerhalb 6 Monate nach Lieferung- und unsere PVC-Folien innerhalb 12 Monate anzuwenden.
- Die Zahlen und Werte dieses Dokumentes dienen nur zur Information.

issued by an electronic system.

